



Overview



HP 1700-8 Switch



HP 1700-24 Switch

Models

HP 1700-24 Switch

J9080A

HP 1700-8 Switch

J9079A

Key features

- Web-managed Layer 2 10/100 switch
- 8- and 24-port models
- Fanless switch for silent operation
- Two dual-personality mini-GBIC slots (J9080A)
- Lifetime warranty*

Product overview

The HP 1700 Switch Series consists of two 10/100 fanless, Web-managed switches that are ideal for open offices that require silent operation or businesses making the transition from unmanaged to managed networks. The HP 1700-24 Switch is a 24-port switch with 22 10/100 ports plus two dual-personality ports. The HP 1700-8 Switch is a small-form-factor switch with seven 10/100 ports and one 10/100/1000 port. The HP 1700 switch series enables increased network capabilities without added complexity.

Features and benefits

Quality of Service (QoS)

- **IEEE 802.1p prioritization:** delivers data to devices by honoring the priority and type of traffic
- **Broadcast control:** allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

Resiliency and high availability

- **IEEE 802.3ad Link Aggregation Control Protocol (LACP):** provides link-level redundancy; support for up to 4 trunks, with up to 7 links (ports) per trunk on the HP 1700-8 Switch, and support for 12 trunks, with up to 8 links (ports) per trunk on the HP 1700-24 Switch.

Manageability

- **Intuitive Web interface:** enables simple management via an easy-to-use Web browser interface for switch configuration, monitoring, and administration
- **Integration with HP PCM:** enables discovery and mapping via HP PCM, available as a free download from the Web
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol provides easy mapping using network management applications



Overview

Layer 2 switching

- **VLAN support and tagging:** support up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups

Security

- **Management password:** provides security so that only authorized access to the Web browser interface is allowed

Monitor and diagnostics

- **Port mirroring:** enables traffic on a port to be simultaneously sent to a network analyzer for monitoring

Ease of use

- **Comprehensive LED display with per-port indicators:** provides an at-a-glance view of status, activity, speed, and full-duplex operation
- **IEEE Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports

Flexibility

- **Small form factor:** ideal for desktop use; is space efficient for deployment flexibility (1700-8 Switch only)
- **Fanless design:** enables quiet operation for deployment in open spaces (selected models)

Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases:** to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

† Hardware warranties replacement for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP Alliance One Advanced Services and Services zl Modules, HP Threat Management Services zl Module, HP AllianceOne Ext zl Mod w/Rvrbd Stlhd, HP E-MSM765zl Mobility Controller and HP Surv Brch Com zl Mod pwrby Msft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at: www.hp.com/networking/warranty.



Technical Specifications

HP 1700-24 Switch (J9080A)	Ports	22 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full 2 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers)											
	Physical Characteristics	<table border="0"> <tr> <td>Dimensions</td> <td>6.74(d) x 17.42(w) x 1.73(h) in. (17.12 x 44.25 x 4.39 cm) (1U height)</td> </tr> <tr> <td>Weight</td> <td>4.38 lb. (1.99 kg)</td> </tr> </table>	Dimensions	6.74(d) x 17.42(w) x 1.73(h) in. (17.12 x 44.25 x 4.39 cm) (1U height)	Weight	4.38 lb. (1.99 kg)							
Dimensions	6.74(d) x 17.42(w) x 1.73(h) in. (17.12 x 44.25 x 4.39 cm) (1U height)												
Weight	4.38 lb. (1.99 kg)												
Memory and Processor	2 MB flash, 2 MB RAM/ROM capacity; packet buffer size: 500 KB												
Mounting	Mounts in an EIA-standard 19-in. telco racks (hardware included)												
Performance	100 Mb Latency	< 4.7 μ s (64-byte packets)											
	1000 Mb Latency	< 3.0 μ s (64-byte packets)											
	Throughput	up to 6.2 million pps (64-byte packets)											
	Switching capacity	8.4 Gbps											
	MAC address table size	8000 entries											
	Environment	<table border="0"> <tr> <td>Operating temperature</td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td>Operating relative humidity</td> <td>15% to 95% @ 104°F (40°C), noncondensing</td> </tr> <tr> <td>Nonoperating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td>Nonoperating/Storage relative humidity</td> <td>10% to 90% @ 149°F (65°C), noncondensing</td> </tr> <tr> <td>Altitude</td> <td>up to 10,000 ft. (3 km)</td> </tr> <tr> <td>Acoustic</td> <td>Power: 0 dB No Fan</td> </tr> </table>	Operating temperature	32°F to 104°F (0°C to 40°C)	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Nonoperating/Storage relative humidity	10% to 90% @ 149°F (65°C), noncondensing	Altitude	up to 10,000 ft. (3 km)	Acoustic
Operating temperature	32°F to 104°F (0°C to 40°C)												
Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing												
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)												
Nonoperating/Storage relative humidity	10% to 90% @ 149°F (65°C), noncondensing												
Altitude	up to 10,000 ft. (3 km)												
Acoustic	Power: 0 dB No Fan												
Electrical Characteristics	Maximum heat dissipation	82 BTU/hr (87 kJ/hr)											
	Voltage	100-127/200-240 VAC											
	Current	0.7/0.4 A											
	Maximum power rating	24 W											
	Frequency	50/60 Hz											
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.											
Safety	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950												
Emissions	FCC Rules Part 15, Subpart B Class A; EN 55022; VCCI; ICES-003 (Canada)												
Immunity	EN	EN 55024, CISPR 24											
	ESD	IEC 61000-4-2											
	Radiated	IEC 61000-4-3											
	EFT/Burst	IEC 61000-4-4											



Technical Specifications

	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC 61000-3-2
	Flicker	IEC 61000-3-3
Management	Web browser	
Notes	Use only supported genuine HP mini-GBICs with your switch. Use only supported genuine ProCurve mini-GBICs with your switch.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UF803E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UF804E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UF806E) 3-year, 24x7 SW phone support, software updates (UF805E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR832E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR833E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR834E) 4-year, 24x7 SW phone support, software updates (UR835E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR836E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR837E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR838E) 5-year, 24x7 SW phone support, software updates (UR839E) 3 Yr 6 hr Call-to-Repair Onsite (UW395E) 4 Yr 6 hr Call-to-Repair Onsite (UW396E) 5 Yr 6 hr Call-to-Repair Onsite (UW397E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU339E) 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HU340E) 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU341E) 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU342E) 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU343E) 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU344E) 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU345E) 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU346E)	

Refer to the HP website at: www.hp.com/networking/services for details on



Technical Specifications

the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1700-8 Switch (J9079A)	Ports	7 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full 1 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
	Physical Characteristics	<p>Dimensions 4.58(d) x 7.73(w) x 1.73(h) in. (11.63 x 19.63 x 4.39 cm) (1U height)</p> <p>Weight 1.19 lb. (0.54 kg)</p>
	Memory and Processor	1 MB flash, 1 MB RAM/ROM capacity; packet buffer size: 144 KB
	Mounting	Horizontal surface mounting only
	Performance	<p>100 Mb Latency < 3.9 μs (64-byte packets)</p> <p>1000 Mb Latency < 2.1 μs (64-byte packets)</p> <p>Throughput up to 2.0 million pps (64-byte packets)</p> <p>Switching capacity 3.4 Gbps</p> <p>MAC address table size 8000 entries</p>
	Environment	<p>Operating temperature 32°F to 104°F (0°C to 40°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 10% to 90% @ 149°F (65°C), noncondensing</p> <p>Altitude up to 10,000 ft. (3 km)</p> <p>Acoustic Power: 0 dB No Fan</p>
	Electrical Characteristics	<p>Maximum heat dissipation 61 BTU/hr (64 kJ/hr)</p> <p>Voltage 100-127/200-240 VAC</p> <p>Current 1.0/0.8 A</p> <p>Maximum power rating 18 W</p> <p>Frequency 50/60 Hz</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adapter part number ordered. Please select the correct power adapter country option.</p>
	Safety	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950



Technical Specifications

Emissions	FCC Rules Part 15, Subpart B Class A; EN 55022; VCCI; ICES-003 (Canada)	
Immunity	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC 61000-3-2
	Flicker	IEC 61000-3-3
Management	Web browser	
Notes	Use only supported genuine HP mini-GBICs with your switch.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UF799E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UF800E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UF802E)	
	3-year, 24x7 SW phone support, software updates (UF801E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (UR824E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (UR825E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR826E)	
	4-year, 24x7 SW phone support, software updates (UR827E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (UR828E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (UR829E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR830E)	
	5-year, 24x7 SW phone support, software updates (UR831E)	
	3 Yr 6 hr Call-to-Repair Onsite (UW392E)	
	4 Yr 6 hr Call-to-Repair Onsite (UW393E)	
	5 Yr 6 hr Call-to-Repair Onsite (UW394E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HR904E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HR905E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR908E)	
	1-year, 24x7 software phone support, software updates (HR907E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR906E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU331E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HU332E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU333E)	



Technical Specifications

3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU334E)
4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU335E)
4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU336E)
5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HU337E)
5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HU338E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols
(applies to all products in series)

General protocols

IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3x Flow Control
RFC 1534 DHCP/BOOTP Interoperation

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)



Accessories

HP 1700 Switch Series accessories

Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
HP 1 m Multimode OM3 LC/LC Optical Cable	AJ834A
HP 2 m Multimode OM3 LC/LC Optical Cable	AJ835A
HP 5 m Multimode OM3 LC/LC Optical Cable	AJ836A
HP 15 m Multimode OM3 LC/LC Optical Cable	AJ837A
HP 30 m Multimode OM3 LC/LC Optical Cable	AJ838A
HP 50 m Multimode OM3 LC/LC Optical Cable	AJ839A
NEW HP 0.5 m PremierFlex OM3+ LC/LC Optical Cable	BK837A
NEW HP 1 m PremierFlex OM3+ LC/LC Optical Cable	BK838A
NEW HP 2 m PremierFlex OM3+ LC/LC Optical Cable	BK839A
NEW HP 5 m PremierFlex OM3+ LC/LC Optical Cable	BK840A
NEW HP 15 m PremierFlex OM3+ LC/LC Optical Cable	BK841A
NEW HP 30 m PremierFlex OM3+ LC/LC Optical Cable	BK842A
NEW HP 50 m PremierFlex OM3+ LC/LC Optical Cable	BK843A
HP 1700-24 Switch (J9080A)	
HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C



Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 1 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ834A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 2 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ835A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 5 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ836A)

Cable type:

50/125 μm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 15 m Multimode
OM3 LC/LC Optical
Cable (AJ837A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 30 m Multimode
OM3 LC/LC Optical
Cable (AJ838A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 50 m Multimode
OM3 LC/LC Optical
Cable (AJ839A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 0.5 m PremierFlex
OM3+ LC/LC Optical
Cable (BK837A)

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um; Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade - Low Smoke Zero Halogen (LSZH) thermoplastic.
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1 m PremierFlex
OM3+ LC/LC Optical
Cable (BK838A)

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 2 m PremierFlex
OM3+ LC/LC Optical
Cable (BK839A)

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5 m PremierFlex
OM3+ LC/LC Optical
Cable (BK840A)

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 15 m PremierFlex OM3+ LC/LC Optical Cable (BK841A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 30 m PremierFlex OM3+ LC/LC Optical Cable (BK842A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP 50 m PremierFlex OM3+ LC/LC Optical Cable (BK843A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC SX Transceiver (J4858C)

Ports
Physical characteristics

1 LC 1000BASE-SX port; Duplex: full only
Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)
Weight: 0.04 lb. (0.02 kg)
Transceiver form factor: SFP

A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.

Environment

Operating temperature: 32°F to 158°F (0°C to 70°C)
Operating relative humidity: 5% to 85%, noncondensing
Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)
Altitude: up to 10,000 ft. (3 km)

Electrical characteristics

Power consumption typical: 0.4 W
Power consumption maximum: 0.7 W

Cabling

Type:

- 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;

Maximum distance:

- 2-220 m (62.5 μm core diameter, 160 MHz*km bandwidth)
- 2-275 m (62.5 μm core diameter, 200 MHz*km bandwidth)
- 2-500 m (50 μm core diameter, 400 MHz*km bandwidth)
- 2-550 m (50 μm core diameter, 500 MHz*km bandwidth)

Cable length: 2-550m

Fiber type: Multi Mode

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessory Product Details

HP X121 1G SFP LC LX Transceiver (J4859C)	Ports	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only
	Physical characteristics	Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)
HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)
	Cabling	Type: <ul style="list-style-type: none">• Either single mode or multimode; 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; Maximum distance: <ul style="list-style-type: none">• 2-550 m (multimode 62.5 μm core diameter, 500 MHz*km bandwidth)• 2-550 m (multimode 50 μm core diameter, 400 MHz*km bandwidth)• 2-550 m (multimode 50 μm core diameter, 500 MHz*km bandwidth)• 2-10,000 m (single-mode fiber)
	Notes	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit www.hp.com/networking

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

