

# LX-350



Economical, 9-pin, 80-column printer from the world's leading dot matrix manufacturer\*.

The highly reliable Epson LX-350 has a mean time between failure of 10,000 operating hours, and is ideal for front and back office applications needing continuous paper or multi-part stationery.

} **A very economical printer to run, the LX-350 helps save money with its high ribbon yield of 4 million characters and its low power consumption. Using just 1.1W in sleep mode and 27W when powered on, the LX-350 is qualified by ENERGY STAR for its excellent energy efficiency.**

{b Easy to integrate, the LX-350 has Parallel, Serial and USB interfaces as standard, and will fit neatly onto desks thanks to its compact design and cable management system.

---

## KEY FEATURES

---

- **High reliability**  
MTBF of 10,000 operating hours
- **Power-efficient**  
1.1W on standby, 27W powered on
- **Economical**  
Ribbon yield of 4m characters
- **Easy integration**  
Parallel, Serial and USB interfaces
- **Compact design**  
Fits neatly onto desks

## PRODUCT SPECIFICATIONS

### TECHNOLOGY

Printing Method	Impact dot matrix
Number of Pins	9 pins
Number of columns	80 columns
Pins	9 Needles

### PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, 15 cpi: 390 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s
Carbon Copies	4 plus one original
Printing Resolution	240 x 144 DPI

### CONNECTIVITY

Interfaces	Bidirectional parallel, USB 2.0, RS-232
------------	---

### PAPER / MEDIA HANDLING

Document Feed	Single sheet rear, Continuous media rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes

### GENERAL

Power consumption	27 Watt, 1,1 Watt (standby)
Product dimensions	348 x 275 x 154 mm (Width x Depth x Height)
Product weight	4,1 kg
Supported Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Supported Humidity	Operation 10% - 80%, Storage 10% - 80%
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	10.000 hours
Print Head Life	400 Million Strokes/Wire
Noise	Operation:53 dB (A)
Memory	128 kB Included
Ribbon Yield	4000000 characters Black Draft

### OTHER FEATURES

Emulations	ESC/P, IBM PPDS
------------	-----------------

### OTHER

Warranty	24 months Carry in Optional warranty extension available
----------	---

## PRODUCT SPECIFICATIONS

### TECHNOLOGY

Printing Method	Impact dot matrix
Number of Pins	9 pins
Number of columns	80 columns
Pins	9 Needles

### PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, 15 cpi: 390 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s
Carbon Copies	4 plus one original
Printing Resolution	240 x 144 DPI

### CONNECTIVITY

Interfaces	Bidirectional parallel, USB 2.0, RS-232
------------	---

### PAPER / MEDIA HANDLING

Document Feed	Single sheet rear, Continuous media rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes

### GENERAL

Power consumption	27 Watt, 1,1 Watt (standby)
Product dimensions	348 x 275 x 154 mm (Width x Depth x Height)
Product weight	4,1 kg
Supported Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Supported Humidity	Operation 10% - 80%, Storage 10% - 80%
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	10.000 hours
Print Head Life	400 Million Strokes/Wire
Noise	Operation:53 dB (A)
Memory	128 kB Included

---

**Ribbon Yield**

4000000  
characters  
Black  
Draft

---

**OTHER FEATURES**

Emulations           ESC/P, IBM PPDS

---

**OTHER**

Warranty             24 months Carry in  
                          Optional warranty extension available

---

---

**LX-350**

---

---

**WHAT'S IN THE BOX**

---

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities
- Software (CD)
- Warranty document
- Power cable
- Ribbon

---

## SUPPLIES

---

- SIDM Black Ribbon Cartridge C13S015637
- SIDM Black Ribbon Cartridge C13S015647

---

## OPTIONAL ACCESSORIES

---

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series  
C12C811141

---

## LOGISTICS INFORMATION

SKU	C11CC24031
EAN code	8715946502939
Country of Origin	Indonesia
Layer	5 Units



Epson Deutschland GmbH  
Schiessstraße 49  
D-40549 Düsseldorf  
Info-Line: 02159 92 79 500  
Telefax: +49 (0) 211 54229-001  
[www.epson.de](http://www.epson.de)

Epson in Österreich  
Info-Line: 01 253 49 78 333  
[www.epson.at](http://www.epson.at)  
Epson in der Schweiz  
Info-Line: 022 592 7923  
[www.epson.ch](http://www.epson.ch)

1. Worldwide sales volume, IDC

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.  
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

**EPSON**<sup>®</sup>