

# AX3000 Wi-Fi 6 Travel Router

**DBR-330**

## Key Features

- Compact, lightweight, and designed for easy portability wherever you go
- Built-in Wi-Fi 6 AX3000 mobile hotspot delivers high-speed, high-performance Wi-Fi to all your connected devices
- Supports multiple methods for sharing Internet connectivity, including routing, Wireless Internet Service Provider (WISP), and 4G/5G hotspot
- USB Type-A port connects to cellular adapters and storage devices
- VPN for convenient, secure remote access
- Support web-based file sharing
- USB Type-C connector for fast charging with USB PD



## User Benefits



### Versatility for Stable Connection

Supports multiple Internet connection methods to achieve high availability of connectivity



### Storage Capacity Expansion

Support microSD/TF Card Slot to expand the storage capacity flexibly



### Join N' Share File Sharing

Share files on the USB drive and microSD card across multiple operating systems for collaborated projects



### Secure Remote Access

Access resources at a remote corporate or branch office conveniently and securely over the Internet using VPN



### Auto LAN/WAN Port

High speed wired local and Internet connectivity with the ability to switch automatically between the two depending on the configured mode



### Best Partner for Smart Life

Enjoy the convenience of mobile Internet and the power of Wi-Fi 6 on all your connected devices at home or on the go

# Technical Specifications

General	
Device Interfaces	1 x Gigabit Ethernet LAN/WAN port (auto-switch between LAN and WAN) 1 x USB Type-C with Power Delivery (PD) for power input 1 x USB Type-A 1 x microSD/TF card slot (CLASS 6 / CLASS 10 / UHS- I) 1 x Reset button
LEDs	Power, Status
IEEE Standards <sup>1</sup>	IEEE 802.11ax/ac/n/g/b IEEE 802.3u/ab
Wi-Fi Data Rates <sup>1</sup>	3000 Mbps (5 GHz up to 2403 Mbps / 2.4 GHz up to 574 Mbps)
Internet Connectivity	Cellular WAN (compatible with D-Link DWM-222W & D501 only) Ethernet WAN: Static IP, Dynamic IP, PPPoE, PPTP, L2TP, DS-Lite, 802.1p & 802.1q VLAN Tagging and Priority Bit Wireless Internet Service Provider (WISP)
Antenna Type	2 x Wi-Fi 2.4 GHz internal antennas 3 x Wi-Fi 5 GHz internal antennas
Functionality	
Security Protocol	<ul style="list-style-type: none"><li>• WPA/WPA2 – Personal</li><li>• WPA2 – Personal</li><li>• WPA2/WPA3 - Personal</li><li>• WPA3 - Personal</li></ul>
File Sharing	Join N' Share (Web-based file sharing function)
Firewall	Stateful Packet Inspection (SPI), Anti-spoofing checking, IP Address Filtering, 1 x DMZ
Software	
Device Management	Web UI
Physical	
Dimensions	120 x 82 x 23.5 mm (4.72 x 3.23 x 0.93 in)
Weight	122 g (4.3 oz)
Power Input <sup>2</sup>	USB Type-C 12 V / 3 A
Operating Temperature	0 to 40 °C (32 to 104 °F)
Storage Temperature	-20 to 65° C (-4 to 149° F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	CE FCC IC
Package Contents	
DBR-330	AX3000 Wi-Fi 6 Travel Router USB-C to USB-C Charging Cable RJ45 Ethernet Cable

1. Maximum wireless signal rate derived from IEEE standard 802.11ax/ac/n/g/b specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors may adversely affect wireless signal range.

2. We recommend using D-Link DPP series power bank (DPP-201) and DCP series GaN charger (DCP-101 & DCP-651) to supply power to the device.