

# AXIS Camera Station S9201 Desktop Terminal

## All-in-one solution for optimal viewing

AXIS Camera Station S9201 Desktop Terminal is a compact all-in-one desktop terminal designed for optimal viewing of high-definition surveillance video where space is limited. The terminal is preloaded with AXIS Camera Station software to minimize installation time and complements AXIS S1032 or AXIS S1048 rack servers to create a high performing surveillance workstation. AXIS S9201 has validated hardware and software components for optimal surveillance experience, and includes three-year hardware warranty with on-site replacement service. AXIS S9201 includes a 22 inch monitor for system overview, as well as a universal keyboard and a computer mouse.

- > **Ease of installation**
- > **AXIS Camera Station software included**
- > **22 inch monitor included**
- > **Validated hardware**
- > **On-site replacement service**



## AXIS Camera Station S9201 Desktop Terminal

<b>Processor</b>	Intel® Core™ i3-7100, 3,9 GHz, 3MB Cache, 2C/4T	<b>Mounting option</b>	VESA 100 x 100 mm (3 15/16 x 3 15/16 in)
<b>Memory</b>	8GB (1x8GB) SO-DIMM 2400 MHz DDR4, non ECC	<b>Operating conditions</b>	0 °C to 35 °C (32 °F to 95° F) Humidity 20–80% (non-condensing)
<b>Storage</b>	M.2 128 GB SATA Solid State Drive	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Monitor</b>	21.5" IPS Wide Viewing Angle WLED Full HD 1920x1080 resolution with anti-glare coating	<b>Approvals</b>	FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KCC KN32 Class B, KN35, EN 62311, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EAC, BSMI, EN 50564, EN 62623, IEC/EN/UL 60950-1
<b>Graphic card</b>	Intel® HD Graphics 630	<b>Dimensions</b>	<b>Monitor:</b> 363 x 528 x 609 mm (14.3 x 20.8 x 2.4 in) <b>Stand:</b> Adjustable x 257 x 225 mm (Adjustable x 10.1 x 8.9 in)
<b>Operating system</b>	Microsoft Windows 10 IoT 2016 LTSB	<b>Weight</b>	<b>Monitor:</b> 6.32 kg (13.90 lb) <b>Stand:</b> 2.79 kg (6.14 lb)
<b>Video streaming</b>	<b>Built-in monitor:</b> Live view and playback: Up to 25 camera split views or 1 x 1080 camera view <b>External monitor:</b> Supports up to 4K	<b>Included accessories</b>	Installation guide, height-adjustable stand, keyboard (international/US), power cable, computer mouse, mousepad
<b>General</b>		<b>Optional accessories</b>	AXIS T8310 Video Surveillance Control Board
<b>Power</b>	155 W AC Input 90–264 V, 50/60 Hz	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Connectors</b>	2x USB 3.0 (side) 2x USB 3.0 (rear) 2x USB 2.0 (rear) 1x RJ45 Ethernet 1x HDMI 1.4 1x Display Port 1.2 1x UAJ (Universal Audio Jack) 1x Audio line out		

## AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on [www.axis.com](http://www.axis.com)

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)