



# Delock Adapter USB Type-C<sup>TM</sup> male > VGA female (DP Alt Mode)

## Description

This Delock adapter is suitable for the connection of a VGA monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface.



20 cm

### **Specification**

- Connectors:
- 1 x USB Type-C™ male >
- 1 x VGA 15 pin female
- Chipset: Realtek RTD2169U
- · VGA port with nuts
- DisplayPort 1.4 specification
- Resolution up to WUXGA 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of analogue video signals
- · USB bus powered
- Plug & Play
- Gold-plated connectors
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- · Colour: black

## System requirements

• Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, iPad Pro (2018),

Linux ex Kernel 4.4, Mac ex OS 10.13

- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

USB-C™ to VGA adapter

# Images





### Item no. 62994

EAN: 4043619629947

Country of origin: China

Package: • Retail Box





| Function:         Plug & Play           Specification:         DisplayPort 1.4           Supported operating system:         Chrome OS           Windows 7 32-bit         Windows 7 64-bit           Windows 8.1 32-bit         Windows 8.1 32-bit           Windows 10 32-bit         Windows 10 32-bit           Windows 10 64-bit         Windows 10 Mobile           Linux Kernel 4.4 or above         Mac OS 10.13 or above           IPlay Pro (2018)         Input:           1 x VGA 15 pin female           Input:         1 x VGA 15 pin female           Input:         1 x USB Type-C™ male           Technical characteristics           Chipset:         Realtek RTD2169U           Maximum screen resolution:         1920 x 1200 @ 60 Hz           Signal transmission:         video           Physical characteristics           Ferrite core:         1 x           Cable length:         20 cm           Connector finishing:         gold-plated | General                     |                           |
|---|-----------------------------|---------------------------|
| Supported operating system:         Chrome OS           Windows 7 32-bit           Windows 8.1 32-bit           Windows 8.1 32-bit           Windows 10 32-bit           Windows 10 64-bit           Windows 10 Mobile           Linux Kernel 4.4 or above           Mac OS 10.13 or above           iPad Pro (2018)           Interface           Output:         1 x VGA 15 pin female           Input:         1 x USB Type-C™ male           Technical characteristics           Chipset:         Realtek RTD2169U           Maximum screen resolution:         1920 x 1200 @ 60 Hz           Signal transmission:         video           Physical characteristics           Ferrite core:         1 x           Cable length:         20 cm           Connector finishing:         gold-plated  | Function:                   | Plug & Play               |
| Windows 7 32-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 64-bit Windows 10 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U Maximum screen resolution: 1920 x 1200 @ 60 Hz Signal transmission: video  Physical characteristics  Ferrite core: 1 x Cable length: 20 cm Connector finishing: gold-plated  | Specification:              | DisplayPort 1.4           |
| Windows 7 64-bit  | Supported operating system: | Chrome OS                 |
| Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U Maximum screen resolution: 1920 x 1200 @ 60 Hz Signal transmission: video  Physical characteristics  Ferrite core: 1 x Cable length: 20 cm Connector finishing: gold-plated   |                             | Windows 7 32-bit          |
| Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz Signal transmission: video  Physical characteristics  Ferrite core: 1 x Cable length: 20 cm  Connector finishing: gold-plated  |                             | Windows 7 64-bit          |
| Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-CTM male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  |                             | Windows 8.1 32-bit        |
| Windows 10 64-bit Windows 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   |                             | Windows 8.1 64-bit        |
| Windows 10 Mobile Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   |                             | Windows 10 32-bit         |
| Linux Kernel 4.4 or above Mac OS 10.13 or above iPad Pro (2018)  Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   |                             | Windows 10 64-bit         |
| Mac OS 10.13 or above iPad Pro (2018)   Interface   Output: 1 x VGA 15 pin female   Input: 1 x USB Type-C™ male   Technical characteristics   Chipset: Realtek RTD2169U   Maximum screen resolution: 1920 x 1200 @ 60 Hz   Signal transmission: video   Physical characteristics   Ferrite core: 1 x   Cable length: 20 cm   Connector finishing: gold-plated   |                             | Windows 10 Mobile         |
| Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  |                             | Linux Kernel 4.4 or above |
| Interface  Output: 1 x VGA 15 pin female Input: 1 x USB Type-CTM male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   |                             | Mac OS 10.13 or above     |
| Output: 1 x VGA 15 pin female Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   |                             | iPad Pro (2018)           |
| Input: 1 x USB Type-C™ male  Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   | Interface                   |                           |
| Technical characteristics  Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  | Output:                     | 1 x VGA 15 pin female     |
| Chipset: Realtek RTD2169U  Maximum screen resolution: 1920 x 1200 @ 60 Hz  Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated   | Input:                      | 1 x USB Type-C™ male      |
| Maximum screen resolution: 1920 x 1200 @ 60 Hz Signal transmission: video  Physical characteristics  Ferrite core: 1 x Cable length: 20 cm  Connector finishing: gold-plated  | Technical characteristics   |                           |
| Signal transmission: video  Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  | Chipset:                    | Realtek RTD2169U          |
| Physical characteristics  Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  | Maximum screen resolution:  | 1920 x 1200 @ 60 Hz       |
| Ferrite core: 1 x  Cable length: 20 cm  Connector finishing: gold-plated  | Signal transmission:        | video                     |
| Cable length: 20 cm Connector finishing: gold-plated  | Physical characteristics    |                           |
| Connector finishing: gold-plated  | Ferrite core:               | 1 x                       |
|   | Cable length:               | 20 cm                     |
| Colours   | Connector finishing:        | gold-plated               |
| Colour: black   | Colour:                     | black                     |