



Industrial IP55 19" Network Cabinet with Integrated Fans, 27U

800 mm (31.5 in.) Depth, Roof-mounted Four-fan Ventilation Unit, Dustingress and Water-jet Protection, Floor-standing. Assembled, Light Gray RAL7035

Part No.: 716130

EAN-13: 0766623716130 | UPC: 766623716130

Industrial Network Cabinet - Floor-standing with IP55 rating - protection against dust ingress and water jets

The IP55 Free-standing Cabinet from Intellinet Network Solutions is equipped to handle challenging environmental conditions. The cabinet's powder-coated steel housing is compliant with IEC standard EN 60529 for safe protection against dust ingress and water jets from any direction. Four sealed cable glands on the bottom panel and pre-punched openings on all sides of the plinth allow for cable entry. To ensure the neatly sealed design, the cabinet comes fully assembled, which also makes your installation quick and convenient. The sturdy 19" steel construction holds heavy rack-mounted equipment up to 1000 kg (2200 lbs.) and can be secured with a 3-point door lock on the swing handle. This IP55 19" cabinet is available in 27U and 42U sizes.

Includes four-fan ventilation unit for efficient cooling

To keep your network equipment cool, this cabinet has a built-in, roof-mounted four-fan ventilation unit. It provides improved performance and longer life to

INTELLINET®

intellinet-network.com

your networking components through reliable cooling and ideal air circulation.

Features:

- IP55-rated for industrial applications: protection against dust ingress and water jets from any direction
- Sturdy, secure steel construction with antistatic powder coating
- Usable installation depth: 157 mm (6.2 in.) to 687 mm (27 in.)
- Maximum load capacity of 1000 kg (2200 lbs.)
- Quiet roof-mounted, four-fan ventilation unit with air filters and a noise level of only 24.9 db (A)
- Efficient heat dissipation for a wide operating temperature up to 50°C (122°F)
- Front and rear steel doors that can be opened 120°
- Earthing kit included
- · Swing handle with three-point door lock and two included keys
- Numbered rackmount space height units
- Bottom panel with four sealed cable-entry opening glands (80 mm/3.2 in. diameter) and five optional fan openings with covers
- Perforated plinth with pre-punched cable entry openings on front, rear, left and right panels
- Ships fully assembled for quick installation
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- IP55 (based on EN 60529)
- ANSI/EIA RS-310-D
- IEC 60297-2
- DIN41494 part 1 and 7

General - Cabinet

- Dimensions (D x W x H): 800 x 600 x 1479 mm (31.5 x 23.62 x 58.23 in.)
- Net weight: 85 kg (187 lbs.)
- Gross weight: 100 kg (220 lbs.)
- Maximum static load: 1000 kg (2200 lbs.)
- Steel thickness: 2 mm on rails, 1.2 mm on other pieces
- Color: light gray RAL7035

General - Fan Unit

- · Four fans with air filters
- Air flow: 85 m³/h (50 cfm) per fan



intellinet-network.com

• Noise level: 24.9 db (A)

• Power cable length: 1.8 m (6 ft.)

• Temperature range: -10 - 50°C (14 - 122°F)

• Operating voltage: 110.0 - 240.0 VAC, 50 - 60 Hz, 10.0 A

Package Contents

• Industrial IP55 19" Network Cabinet with Integrated Fans, 27U

Roof-mounted four-fan ventilation unit

• Rack-mounting material: 10 M6 screws, 10 M6 cage nuts and 10 washers

Two keys

This product is also available in size 42U as model number 716147.











intellinet-network.com

