



2-Port USB Power Delivery Mini Wall Charger - 20 W

USB-C PD Port up to 20 W, USB-A QC 3.0 Charging Port up to 18 W, Compact Format, EU Plug, White

Part No.: [406307](#)

EAN-13: 0766623406307 | UPC: 766623406307

PD Charger - small but powerful two-in-one dual-port USB-C and USB-A fast-charger

With one 20 W USB-C Power Delivery (PD 3.0) port and one 18 W Quick Charge (QC 3.0) USB-A port, you're ready to charge your phones, tablets and more, super-fast. If you use both ports simultaneously, you can still charge your devices very fast with a shared 15 W.

Compact

All this power comes installed in a pocket-friendly format to make it the ideal travel companion.

Superior safety

Overload, overcurrent and overheating protection guarantee maximum safety for you and your devices.

Universal compatibility

Charge virtually all your mobile devices at maximum speed, from Bluetooth[®] headphones to smartphones to high-end tablets.

High-speed charging optimized for iPhone[®]

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Use the 20 W USB-C port to charge your iPhone 13 from 0% to 50% in just 25 minutes.

Features:

- Pocket-friendly but powerful 2-in-1 fast-charger for phones, tablets, portable game consoles and other mobile devices
- USB-C Power Delivery (PD 3.0) port delivering up to 20 W
- Quick Charge™ (QC 3.0) USB-A port delivering up to 18 W
- 15 W shared power output when using both ports simultaneously
- 20 W PD port ideal for charging the iPhone® 12 and 13 series at maximum speed
- Overload, overcurrent and overheating protection
- Compact, portable and lightweight design for easy travel
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- FCC
- ETL
- UKCA

Electrical

- AC input: 100.0 - 240.0 V; 0.7 A; 50 - 60 Hz
- Voltage/current settings (maximum):
 - USB-C PD 20.0 W output:
 - 5.0 V / 3.0 A
 - 9.0 V / 2.22 A
 - 12.0 V / 1.66 A
 - USB-A QC 3.0 18.0 W output:
 - 5.0 V / 3.0 A
 - 9.0 V / 2.0 A
 - 12.0 V / 1.5 A
 - USB-C and USB-A 15.0 W shared simultaneous output:
 - 5.0 V / 3.0 A
- Compatible devices including but not limited to: iPhone® 13, 13 Pro, 13 Pro Max, 13 mini, SE 2022, 12, 12 mini, 12 Pro, 12 Pro Max, X, XS, XS Max, XR, 8 Plus, 8; iPad® 10.2" / iPad mini® 8.3" / iPad Pro® 12.9" / iPad Pro 10.5" / iPad Pro 11" / iPad mini 5, Samsung® Galaxy S22, S22 Ultra, S21, S20, S10, S10

Plus, S10E, S9, S9 Plus, Note 9, S8, S8 Plus, Note 8, S7 Edge, S7, S6 Edge plus, Note 5; Google Pixel™ 6, 6XL, 5, 5XL, 4, 4 XL, 3, 3 XL; LG V60 ThinQ, V50 ThinQ, V50, V40 ThinQ, V35, V30+, V30, G8 ThinQ, G8, G6; AirPods® and AirPods Pro®, phones from Huawei®, Asus®, Sony® and more

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

Physical

- Dimensions (L x W x H): 80 x 30 x 43 mm (3.15 x 1.18 x 1.7 in.)
- Net weight: 44 g (1.55 oz.)
- Gross weight: 60 g (2.12 oz.)
- Housing: plastic

Operating Environment

- Operation temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -20 - 65°C (-4 - 149°F)
- Humidity (noncondensing): 10 - 90%

Package Contents

- 2-Port USB Power Delivery Mini Wall Charger - 20 W
- Instructions



