

## ICY BOX IB-DK4031-CPD Combo adapter for notebooks




## Key features

- Extends 1x USB Type-C™ to 3x further interfaces
- Input (to Notebook / PC): USB 3.0 Type-CTN
- Output:

1x USB 3.0 Type-A (backwards compatible to USB 2.0) 1x High Speed HDMI® A-Type (up to 3840x2160@30Hz)
1x USB Type-C™ power input to charge notebooks or USB 3.0 data transfer up to 5 Gbit/s

USB Type- $C^{TM}$  combo adapter The USB Type- $C^{TM}$  to HDMI Multi-Docking-Adapter is designed for connecting a USB Type-C™ embedded device (laptop, desktop etc.) that also supports DP alternate mode to a HDMI embedded device (television, monitor and etc.). This adapter's output resolution is up to 3840x2160@30 Hz. No need to install extra drivers, just plug & play.

Additionally you can charge your PC by inserting the power adapter came with your PC into the USB-C connector and process data link via USB 3.0 Type-A connector at the same time. Besides, when you don't charge any device from USB Type-C™ connector, you can process data link via this port.



Technical data

Tranferrate

IB-DK4031-CPD Model 60070 Article No. EAN 4250078164081 Brand ICY BOX Colour Black Material PC + ABS

Main Chipset (Video): Parade PS176 Input interface Main Chipset (HUB controller): VIA-Labs

VL210-Q4 QFN-48

VL100 DP Alt-mode Type-C™ Controller QFN-40 Output interface

1x USB Type- $C^{TM}$  (UFP) from Host PC 1x USB Type- $C^{TM}$  (DFP), for PC power delivery up to 20V@3A or USB 3.0 data transfer up

to 5 Gbit/s

1x High Speed HDMI®, 1x USB 3.0 Type-A (DFP)

USB 3.0 up to 5 Gbit/s HDMI® resolution Up to 3840x2160@30Hz

Power supply Bus powered via USB Type-C™ port Operating system Windows® 10 and above

Mac OS® 10.11.x and above, Chrome OSTM PC with USB Type- $C^{TM}$  interface supporting

VESA DisplayPort alternate mode System Requirements

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries Packing content: 1x IB-DK4031-CPD

Logistical data

Packing unit/carton: 60 pcs/carton Dimension/carton: 418x325x305 mm Total weight/carton: 7.9 kg/carton Dimension/packing: 200x105x25 mm Gross weight/packing: 0.112 kg Dimension/product: 50x58x10 mm Net weight/product: 0.037 kg Country of origin: China

RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany Telephone: +49-(0)4102 - 468 900 (Sales) • Fax: +49-(0)4102 - 468 901 • www.raidsonic.de Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

