



## Cat6a Shielded Desktop Patch Panel

12-Port, FTP, 90° Top-Entry Punch-Down Blocks, Black

Part No.: 720915

EAN-13: 0766623720915 | UPC: 766623720915

### Cat6a Shielded Desktop Patch Panel — proper network connections, no rack or cabinet required

The Intellinet Network Solutions Cat6a Shielded Desktop Patch Panel helps IT staff create the right Cat6a-compliant network for their organization. Whether wiring connection points for all compatible equipment or adding more ports to the network with the latest Ethernet cabling standard available, the Cat6a Shielded Patch Panel helps the network grow and evolve. The panel is designed for fully shielded twisted-pair Cat6a wires, and compatible Krone punch-down tools will help get ports wired quickly. The Intellinet Network Solutions Cat6a Shielded Desktop Patch Panel adheres to current industry standards.

#### Features:

- Solid and reliable terminations for copper cable, featuring a minimum of 3-micron gold-plated jack contacts
- Top-entry punch-down blocks to simplify installation
- Compatible with Krone punch-down tools
- Supports 23 to 26 AWG stranded and solid wire
- For use with fully shielded twisted pair (FTP) Cat6a network cable
- Ideal for Ethernet, Fast Ethernet and Gigabit Ethernet network applications
- Lifetime warranty

#### Specifications:

##### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000Base-T Gigabit Ethernet)
- ISO/IEC 11801

*For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).*

*All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.*

- ANSI/TIA
- 568 A/B color-coded

#### Certifications

- CE
- RoHS
- FCC

#### Physical

- Dimensions: 128 (L) x 212 (W) x 44 (H) mm (5.04 [L] x 8.35 [W] x 1.73 [H] in.)
- Weight: 868 g (1.91 lbs.)

#### Environmental

- Operating temperature: 10 – 60°C (32 – 140°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -40 – 70°C (-40 – 158°F)

#### Package Contents

- Cat6a Shielded Desktop Patch Panel
- Grounding wire
- Quick Install Guide



